



POWERTOOLS SWEDEN AB
 Kvartergatan 10
 749 40 ENKÖPING
 SWEDEN
 Telephone: +46171 663 000
 Email: powertools@powertools.se



HIGH TORQUE OIL FREE SHUT OFF AIR COMPOSITE WRENCH (ANGLE TYPE, EXTENDED LEVER START)

Specification:

Model No.	Free Speed (r.p.m)	Torque Range		Weight (g)	Length (mm)	Dia. (mm)	Air Consumption (m ³ /min)	Standard Deviation	Noise Level (±2dBA)	Min. air hose bore (mm)	Fastening Capacity	
		kgf-cm	Nm								Machine Screw	Tapping Screw
HAWFHE180	770	50-180	5-18	1,550	430	43	0.65	±3%	78	8.0	M6.8~M9.3	M5.3~M7.2
HAWFHE250	430	30-250	3-25	1,750	430	43	0.65	±3%	78	8.0	M5.0~M10.0	M4.0~M8.0
HAWFHE400	250	50-400	5-40	1,750	430	43	0.65	±3%	78	8.0	M8.8~M11.8	M6.8~M9.7
HAWFHE600	180	250-600	25-60	2,000	500	43	0.65	±3%	78	8.0	M8.8~M13.0	M6.8~M10.5

Recommend Air Pressure: 90 psi (6.3kg/cm²)